

DYNAMIC OPV HI-GLOSS

Water based supergloss coating

KEY CHARACTERISTICS

- For board and paper
- For packaging and commercial printing
- Suited for single sided application
- Fast drying allows high print speed
- Good block resistance
- Good rub resistance
- Solid content @ 44%
- Viscosity : 65-85s @30°C DIN #4 cup
- Density : approx 1.05 g/ml @25°C
- Colour : Milky white emulsion

FEATURES AND BENEFITS

- Excellent gloss (70-75 on CCNB BOARD)
- Outstanding brilliance

INSTRUCTIONS FOR USE

Use directly from container. It is highly recommended to shake/stir the contents before use for the optimum performance of the varnish.

Do not leave product expose to air. Some ingredients may evaporate and this will affect the physical properties and performance of the product.

TRANSPORT & STORAGE

Store at room temperature with container tightly closed when not in use in a cool, ventilated area. Protect from direct sunlight and keep away from heat sources.

RECOMMENDED AUXILIARIES

Coating cleaner : special cleaner for the coating blankets and rollers

Anilox cleaning gel : to remove dried coating from the cells of the anilox roller

Packing available: 25 kg



LINE OA

034-871604-6

kpnsale@kpn2552.com

 kpngraphics.co.th